



FabricMaster HD™

FabricMaster HD Upholstery Pre-spray is designed for the upholstery cleaning craftsperson. While many cleaners use carpet pre-sprays on upholstery, the craftsperson recognizes the important differences between upholstered fabrics and carpeting, as well as the soils that build up in them. This specialized formula is specifically designed to break down, dissolve, and emulsify the soils and spills most common to upholstery fabrics – body oils, hair treatments, airborne oils, shoe scuffs, spilled food and beverages, crooked colors from clothes, newsprint, and pet hair.



ing, the user s
ct for its intend

Net Contents:
1 gallon (3.78 liters)



Fabric designed
While m
on uphol
importan
and carp
in them.
formula
but then
for use o
all of thi
ammoni
surfacta
designe
the soils
fabrics.

should thoroughly review the material safety data sheet for this product and follow recommendations for mixing, application, disposal, and the use of any applicable personal protective equipment (PPE). The manufacturer, distributor, and seller of this product warrant that the chemical contained herein conforms to its standard specifications.

er HD Upholstery Pre-spray is the upholstery cleaning craftsperson. Cleaners use carpet pre-sprays, the craftsperson recognizes the differences between upholstered fabrics, as well as the soils that build up.

UpholstericMaster HD is a self-neutralizing cleaner that cleans with the power of alkalinity, self-neutralizes as it dries. It is designed for synthetic upholstery fabrics. It does not sacrifice the cleaning power of odorless solvents combined with specialized solvents and enzymes. This specialized formula is specifically designed to break down, dissolve, and emulsify most spills common to upholstery such as body oils, hair treatments, airborne pollutants, cuffs, spilled food and beverages, stains from clothes, newsprint, and pet odors.

UpholstericMaster HD is a low foaming formula that leaves a sticky residue. A special ingredient allows the fabric dry faster after cleaning which reduces the chances for overwetting based

Directions:

1. Vacuum.
2. Always wear gloves.
3. For best results, spray 4 pats of product onto the fabric.
4. Apply evenly.
5. Allow to dry.
6. Agitate.
7. For best results, utilize a wet vac.
8. For best results, consider a mister.

fabricMaster HD contains the same
ng additive that is in our famous
Pro XP spotting agent, effectively
any beverage spills without the need
tain treatments.


1. Thoroughly before starting cleaning process.
 2. all cleaning solutions in an inconspicuous test area prior to application.
 3. um soil, mix 1 part **FabricMaster HD** with 2 ounces of solution with 1 gallon of water)
 4. t heavy soiling, mix 1 part solution with 1 ounces of solution with 64 ounces of water)
 5. -held pump up or trigger sprayer in an ang mist across the entire area of the fabric
 6. r 2-3 minutes. Be careful not to overspray
 7. sehair brush or bonnet mitt.
 8. extract area with **CleanMaster RinseOut**
 9. **DrilMaster DrillMaster 2 or 3 Upholstery**
 10. g, especially in humid environments,
 11. e of an axial, centrifugal, or downdraft air
 12. ning.

Acciones:

- completamente antes de comenzar el proceso
za.

antes de probar todas las soluciones de limpieza
a oculta la estabilidad del color antes de la
n.

edad leve a mediano, mezcle una parte Fabric-
D con tres partes de agua (42 onzas de solución
alón de agua) en el pulverizador. En caso de
fuerte, no diluir. Utilice recta.
on bomba de mano hacia arriba o pulverizador
en una niebla incluso, la superposición a través
l área de la tela que se limpia.
habitar durante 2-3 minutos. Tenga cuidado de
ar el exceso de pulverización o neblina.
un cepillo de crin o manopla del capó.
nener los mejores resultados extraer zona con
CleanMaster utilizando el HydraMaster DriMas-
ramiento de limpieza de tapicería.
secado más rápido, especialmente en ambientes
, considerar el uso de un motor axial, el aire
o de corriente descendente después de la



ts: Glycol ether DB (112-34-5), Sodium
ate(5324-84-5), sodium thiosulfate (7772-98-7),
ethanolamine (141-43-5), alcohol ethoxylate (68954-96-1)

Prosecutions and First A

ldren. Contact may cause Wear gloves and safety to avoid any contact with skin in concentrate form. Use areas. In case of eye contact, plenty of water. If irritation attention. In case of skin irritation, water. If ingested, drink large seek medical attention. Re- e of inhalation. See Material DS): www.hydramaster.com/ Safety and regulatory information.

Precauciones y Primeros Auxilios

!
n de los niños.
ar irritación
uantes y gafas
anipule para evitar cualquier
el contacto con la piel en
Usar sólo en áreas bien
contacto con los ojos, lávelos
undante agua. Si la irritación
ón médica. En caso de
r con abundante agua. Si se
ntidades de agua y buscar
adar al aire fresco en caso de
seguridad (MSDS): www.sanitas.com
s para mayor seguridad y

HydraMaster
www.hydramaster.com
425 775 7272



Part # 950-230-S Art 950-230-S B1 10149-01028