







NASHUA[°] 322 MULTI-PURPOSE FOIL TAPE

48mm x 46M ITEM NO. 617001B 24 rolls/case 27 cases/pallet UPC: 7-42366-99983-2

2.5in x 50Yd ITEM NO. 617004B 16 rolls/case 27 cases/pallet UPC: 0-33656-30600-4

72mm x 46M ITEM NO. 617020B 16 rolls/case 27 cases/pallet UPC: 0-33656-30700-1

FOR MORE INFORMATION ON NASHUA® 322 OR OTHER NASHUA® BRAND PRODUCTS FOR THE HVAC MARKET, CONTACT YOUR AREA SALES REPRESENTATIVE

Nashua[®] **322** Multi-Purpose Foil Tape

Berry Plastics Corporation, the industry leader for innovative materials for HVAC, is proud to offer Nashua® 322 Multi-Purpose Foil Tape. Nashua® 322 features a thick, heavy-duty foil and performs well in virtually all duct sealing applications and is suitable for vapor barrier sealing on ductwrap, FSK insulation, and fiberglass duct board.

SPECIAL FEATURES

- High tack adhesive forms an aggressive bond
- Conformable to fit corners & joints
- UL 723 Classified
- Resists UV, humidity and mold
- Provides long-term anchorage and a durable seal
- Eco-Friendly release liner made from unbleached natural kraft paper
- Low VOC content
- Can contribute toward EA Credit 1 (Optimize Energy Performance) and EQ Credit 4.1 (Low Emitting Materials, Adhesives and Sealants) under LEED[®]

Thickness: 5.0 mils (88.9 μ) Adhesion to Steel: 55 oz/in (127 N/cm) Adhesion to Backing : 130 oz/in (14.23 N/cm) Tensile Strength: 15 lb/in (26.27 N/cm) Installation Temperature: 40 to 200° F (4 to 93° C) VOC Content: <1 g/L





tapes.berryplastics.com

For more information: 25 Forge Parkway Franklin, MA 02038 Phone 508.918.1600 • Fax 508.918.1901 Toll Free US: 1.800.343.7875

028HJ_06-12