

Quake HD™

High Definition Cleaning Carpet Prespray & Traffic Lane Cleaner

with
TRITANOL
1+1=3
Exclusively from
CleanMaster

Uncompromising cleaning power is now available in a VOC compliant formula with Quake HD. Quake HD is a VOC compliant formula that contains the industry exclusive component Tritanol™ - an integrated blend of specialized polymers, organic sequestrants, and surfactants. With the unprecedented cleaning power and performance of Tritanol™, you will experience deep restorative cleaning in high definition.


CLEANMaster™
A HydraMaster / U.S. Products Brand




If for any reason you are not thrilled with the performance of Quake HD return it to your distributor and we'll get you a product that does.

Net Contents:
One U.S. Gallon (3.78 liters)

Before using, the user shall determine the suitability of this product for its intended use, and user assumes all risk and liability whatsoever in conjunction therewith. The user should thoroughly review the material safety data sheet for this product and follow recommendations for mixing, application, disposal, and the use of any applicable personal protective equipment (PPE). The manufacturer, distributor, and seller of this product warrant that the chemical contained herein conforms to its standard specifications.



Read the
MSDS
Scan here



Lot:

Contents: Proprietary polymers, diethylene glycol butyl ether (112-34-5), sodium tripolyphosphate (7758-29-4), sodium alkylnaphthalenesulfonate blend (trade secret), proprietary surfactant, potassium hydroxide (1310-58-3), water (7732-18-5), proprietary fragrance.

Seller's and manufacturer's liability for any and all losses or damages resulting from any cause whatsoever shall in no event exceed the purchase price of this product, with respect to which losses or damages are claimed. The manufacturer and seller make no representation or warranty, including merchantability or any other kind, expressed or implied. The foregoing may not be altered except by written agreement by officers of the manufacturer.

Experience cleaning in high definition, even when you are cleaning heavily soiled and grimy carpets. Quake HD is a VOC compliant formula that contains the industry exclusive component Tritanol™ - an integrated blend of specialized polymers, organic sequestrants, and surfactants. With the unprecedented cleaning power and performance of Tritanol™, you will experience deep restorative cleaning in high definition. It just works better! It dissolves and cuts through oxidized oils and grease without the use of harsh solvents and is excellent at emulsifying particulate soils. The synergistic combination of solvents, surfactants, boosters, and high pH alkaline cleaning agents will quickly remove the toughest soils found in restaurants, apartments, and restoration cleaning jobs. Quake HD is a super-concentrated pre-spray, and is designed to be used at 1 part solution to 8 to 24 parts water depending upon soiling conditions. Quake HD will help you to restore the appearance of dirty and neglected carpets and make you the hero in the eyes of the customer. It is formulated to be used on synthetic carpets, specifically, nylon that have been neglected or require constant cleaning. It has a ready-to-use pH of 11.5 – 12.0, so it is not recommended to be used on warranted residential carpets that have been properly maintained. Quake HD is low foaming, has a mild fragrance and rinses free of the carpet for low residue cleaning. It also contains anti-resoiling additives which keep the carpet cleaner longer and does not leave sticky residue.

Directions:

1. Always pre-test all cleaning solutions in an inconspicuous area for colorfastness prior to application.
2. For increased efficiency, apply Quake HD with injection sprayer to take advantage of solution pressure and heat created by your high performance portable extractor or truckmount. You can also use a "pump-up" pressure sprayer, or electric or battery powered sprayer. Apply in even overlapping patterns.
3. Prespray with 1 part Quake HD mixed with 24 parts hot water. For extreme soiling, mix Quake HD 1 part solution to 8-12 parts water. For standard injection sprayer, mix one quart water with four quarts of Quake HD into 5 quart container.
4. For carpets with high levels of caked-on grease and oil contamination, consider boosting by adding two ounces of GreaseBreaker with each mixed gallon of Quake HD.
5. Extract with a compatible alkaline extraction detergent or acid/neutralizing rinse. For faster cleaning, reduced fatigue, and more effective soil removal, extract with the RX-20 Rotary Extraction Tool. In furniture dense environments use the Evolution cleaning wand.
6. For faster drying, especially in humid environments, consider the use of an axial, centrifugal, or downdraft air mover after cleaning.

Instrucciones:

1. Siempre antes de probar todas las soluciones de limpieza en un área poco visible la estabilidad del color antes de la aplicación.
2. Para una mayor eficacia, aplicar Quake HD con el rociador de la inyección para tomar ventaja de la presión de la solución y el calor creado por su alto rendimiento extractor portátil o Truckmount. También puede utilizar una "bomba-up" pulverizador o rociador potencia eléctrica o la batería. Aplicar en la superposición de patrones, incluso.
3. Prespray con 1 parte de mixta Quake HD 24 partes de agua caliente. En caso de suciedad extrema, mezcle una solución de Quake HD parte a 8.12 partes de agua. Para el pulverizador de inyección estándar, mezclar un litro de agua con cuatro cuartos de Quake HD en un recipiente de 5 cuartos.
4. Para las alfombras con altos niveles de apelmazan en la grasa y la contaminación por petróleo, considere aumentar mediante la adición de dos onzas de GreaseBreaker con cada galón de mezcla de Quake HD.
5. Se extrae con un detergente compatible extracción alcalina o ácida / neutralizar enjuague. Para una limpieza más rápida, reducción de la fatiga y la eliminación de la suciedad más efectivo, el extracto con el RX-20 Herramienta de extracción de Rotary. En muebles de ambientes densos utilizar la varita de limpieza Evolución.
6. Para un secado más rápido, especialmente en ambientes húmedos, considerar el uso de un motor axial, aire centrífugo, o corriente descendente después de la limpieza.

Precautions and First Aid:

Keep out of reach of children. Contact may cause skin and eye irritation. Wear gloves and safety glasses when handling to avoid any contact with eyes and contact with skin in concentrate form. Use only in well ventilated areas. In case of eye contact, immediately flush with plenty of water. If irritation persists, seek medical attention. In case of skin irritation, flush with plenty of water. If ingested, drink large quantities of water and seek medical attention. Remove to fresh air in case of inhalation. See Material Safety Data Sheet (MSDS): www.hydramaster.com/msds for additional safety and regulatory information.

Precauciones y Primeros Auxilios:

Mantener fuera del alcance de los niños. El contacto puede causar irritación cutánea y ocular. Use guantes y gafas de seguridad al manejar para evitar cualquier contacto con los ojos y el contacto con la piel en forma de concentrado. Use sólo en áreas bien ventiladas. En caso de contacto con los ojos, lávelos inmediatamente con abundante agua. Si la irritación persiste, busque atención médica. En caso de irritación de la piel, lavar con abundante agua. Si se ingiere, beber grandes cantidades de agua y busque atención médica. Sacar al aire libre en caso de inhalación.

Ver Hoja de Seguridad (MSDS): www.hydramaster.com/msds para mayor seguridad y normativas.

HydraMaster/U.S. Products
www.hydramaster.com
425.775.7272
Part # 950-127-S Art 950-127-S-R2



8 10149 01083 5