

5477NB

7-1/4" Hypoid Saw

POWER : Powerful 15 AMP motor for increased productivity

TECHNOLOGY : Oil bath technology and sealed gear housing for less maintenance

PERFORMANCE : High quality, heat treated hypoid gears for long lasting performance

CAPACITY : 0°-51.5° bevel capacity with positive stops at 45° and 51.5° for truss and rafter cut-outs

INCLUDES : Carbide tipped blade and wrench



ABOUT MODEL

Makita's 7-1/4-Inch Hypoid Saw (model 5477NB), combines a powerful 15 AMP motor and Makita's efficient hypoid gears with ease-of-use features for more power, better performance and superior cuts. The 5477NB is engineered for framing walls, siding, roofs and floors using a range of dimensional lumber and engineered lumber, including OSB, LVL, PSL, plywood, and more. It is ideal for framers, builders, carpenters, and general contractors seeking a best-in-class 7-1/4-Inch hypoid saw.

The 5477NB has a powerful 15 AMP motor with ball bearing construction for increased productivity. Makita's efficient hypoid gears have greater surface contact and deliver more constant power. The oil bath technology and sealed gear housing are engineered for less maintenance, with high quality heat treated hypoid gears for long lasting performance.

The 5477NB includes a Makita 7-1/4-Inch General Contractor Framing Blade with Advanced Tooth Design. The carbide tips are specifically set to withstand the harshest conditions such as plowing through nail-embedded wood. The blade is designed with special Makita heat vents strategically set to dissipate heat and increase performance.

FEATURES

- Hypoid gears deliver more power and have greater surface contact than conventional worm drive gears
- Powerful 15 AMP motor for increased productivity
- Oil bath technology and sealed gear housing for less maintenance
- 0°-51.5° bevel capacity with positive stops at 45° and 51.5° is ideal for truss and rafter cut-outs
- High quality, heat treated hypoid gears are engineered for long lasting performance
- Large cutting capacity (2-3/8" at 90°; 1-3/4" at 45° and 1-9/16" at 50°)
- Lower guard design improves performance when making bevel and narrow cuts
- Oversized top handle for better fit and added comfort
- Large levers for fast bevel and depth adjustments
- Push button spindle lock for easy blade changes



INCLUDES

(1) 7-1/4" 24T Framing Blade, General Contractor (D-45989-1)

(1) Hex Wrench (783204-6)

SPECS

Blade Diameter :	7-1/4"
Arbor :	5/8"
Max. Cutting Capacity (at 90°) :	2-3/8"
Max. Cutting Capacity (at 45°) :	1-3/4"
Max. Cutting Capacity (at 50°) :	1-9/16"
No Load Speed :	4,500 RPM
Watts Out :	2,300
AMPS :	15
Overall Length :	17-3/8"
Net Weight :	14.3 lbs.
Power Type :	Corded
Shipping Weight :	18.07 lbs.
UPC Code :	088381-096133

RESOURCES & MEDIA

[5477NB Instruction Manual](#)

[5477NB Parts Breakdown](#)

[5477NB Flyer English](#)

PRODUCTS RELATED TO 5477NB

Page 1 of 2



5377MG
7-1/4" Magnesium Hypoid Saw



XSR01PT
18V X2 LXT® (36V) Brushless Rear Handle 7-1/4" Circular Saw Kit



GRP-CSB-006
7-1/4" Wood