

# SLURRY

VACUUM AND PUMP  
SLURRY MANAGEMENT SOLUTION

## STANDARD SPECIFICATIONS: **SLURRY PRO**

- Dual Motor - 110/1/60, 200 CFM, 3.2Hp and 98" H2O
- 38 GPM Return Pump Designed for Abrasive Solids
- 32 Gallon Liquid Collection Capacity
- Compression Cast **"Bulletproof"** Composite Modular Housing
- 44 ft<sup>2</sup> of Hydrophobic Filtration - 99% Efficient @ 0.5 Microns
- 2" Vacuum Inlet
- Intermittent Duty Operation
- Bottom Gravity Feed Discharge with Blast Gate
- Positive Closure Float for Liquid Fill Shut Off

## SLURRY PRO



**SIMPLIFYING SLURRY.**

[www.ruwac.com](http://www.ruwac.com)  
**Ruwac** USA

THE FINE DUST EXPERTS

CONTACT US TODAY FOR PRICING AND AVAILABILITY

**413-532-4030**

## AVAILABLE UPGRADES:

- 42" Floor Sweep
- 32" Floor Sweep
- 20" Floor Tool, Wand and Hose Kit

**Ruwac**

**INDUSTRIAL VACUUM SOLUTIONS**