



SAFETY DATA SHEET

Issue Date 27-Dec-2020

Revision Date 27-Dec-2020

Version 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier

Product Name Endura EN230 Series Acrylic Latex Caulk White

Other Means of Identification

SDS # 26510646

Product Code 0770 Series

Recommended Use of the Chemical and Restrictions on Use

Recommended Use Premium elastomeric, multi-purpose sealant – offers water clean-up.

Details of the Supplier of the Safety Data Sheet

Supplier Address

AramSCO Inc.
1480 Grandview Ave.
Paulsboro, NJ 08066
USA
www.aramSCO.com

Emergency Telephone Number

Company Phone Number 800-767-6933

Emergency Telephone United States: 1-800-535-5053 (INFOTRAC – 24 hours, 7 days a week)
International: 1-352-323-3500 (INFOTRAC – 24 hours, 7 days a week)
Poison Control 1-800-222-1222 (24 hour)

2. HAZARDS IDENTIFICATION

Classification

This chemical does not meet the hazardous criteria set forth by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). However, this Safety Data Sheet (SDS) contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.

The product contains no substances which at their given concentration, are considered to be hazardous to health

Appearance White & Various Other
Colors

Physical State Smooth paste

Odor Mild acrylic

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Calcium Carbonate	1317-65-3	<45
Acrylic Emulsion	MIXTURE	<45
Benzoate Ester	Proprietary	<10
Titanium dioxide	13463-67-7	<2.0
Non-hazardous Ingredients*	Proprietary	<5
Ammonium Hydroxide	7664-41-7	<0.25
Carbon Black	1333-86-4	0-0.25
Petroleum Hydrocarbon	64742-48-9	<0.75

* Unlisted ingredients are not considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200). (Calcium Carbonate, Titanium Dioxide) Inhalation of particulates unlikely due to product's physical state. (Carbon Black) May be present in colors other than White.

4. FIRST AID MEASURES

First Aid Measures

General Advice	Provide this SDS to medical personnel for treatment.
Eye Contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Seek immediate medical attention/advice.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If irritation persists, seek medical attention.
Inhalation	Remove to fresh air. If breathing difficult, leave area to obtain fresh air. If breathing remains difficult, get medical attention.
Ingestion	Do not induce vomiting unless directed by medical personnel. If vomiting occurs, lean patient forward to maintain an open airway & prevent aspiration. Get immediate medical attention.

Most Important Symptoms and Effects, both Acute and Delayed

Symptoms	Prolonged or repeated skin contact may result in dermatitis (red, dry skin). Direct contact with eyes may cause temporary irritation. Exposed individuals may experience eye tearing, redness and discomfort. Irritating to mouth, throat, and stomach if ingested. May cause gastrointestinal irritation, nausea, diarrhea, and vomiting. Overexposure to vapors during application and curing may mildly irritate respiratory tract and result in coughing and sneezing.
-----------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Indication of any Immediate Medical Attention and Special Treatment Needed

Note to Physicians	Provide general supportive measures and treat symptomatically. May aggravate pre-existing skin disorders.
---------------------------	-----------------------------------------------------------------------------------------------------------

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon dioxide (CO₂). Dry chemical. Water spray (fog). Foam. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Product is combustible & may ignite if exposed to high temperature or direct flame.

Hazardous Combustion Products

Carbon, titanium & iron oxides, depending upon formulation.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to keep fire-exposed containers cool.

6. ACCIDENTAL RELEASE MEASURES**Personal Precautions, Protective Equipment and Emergency Procedures****Personal Precautions**

Wear protective clothing as described in Section 8 of this safety data sheet.

Other Information

Small Spills: 1 drum or less – Level D Equipment (gloves, chemical resistant apron, boots & eye protection).

Large Spills: Rubber gloves, rubber boots, face shield & Tyvek suit as a minimum. Minimum level of PPE for releases in which the oxygen level is < 19.5% or is unknown, should be Level B: triple gloves (rubber gloves & nitrile gloves over latex gloves), chemical resistant suit, fire-retardant clothing & boots, hard hat & self-contained breathing apparatus.

For Emergency Responders

Restrict access to spill area.

Environmental Precautions

Minimize use of water to prevent environmental contamination. Prevent spill or rinse from contaminating storm drains, sewers, soil or groundwater. Do not allow discharge containing this material to enter streams, ponds, estuaries, oceans or other waters unless in accordance w/ requirements of National Pollutant Discharge Elimination System (NPDES) permit & permitting authority has been notified in writing prior to discharge. Do not allow discharge containing this material to enter sewer systems w/o previously notifying local sewage treatment plant authority. For information, contact State Water Board or EPA Regional Office

Other: U.S. regulations may require reporting of spills of this material reaching surface waters if sheen is formed.

Methods and Material for Containment and Cleaning Up**Methods for Containment**

Prevent further leakage or spillage if safe to do so. Use absorbent material to contain spill.

Methods for Cleaning Up

Sweep up absorbed material and shovel into suitable containers for disposal. Wash area with soap and water. For waste disposal, see section 13 of the SDS.

7. HANDLING AND STORAGE**Precautions for Safe Handling****Advice on Safe Handling**

Avoid breathing vapors. Use only with adequate ventilation. Open windows & doors to ensure fresh air cross-ventilation during application and curing. Wash thoroughly with soap and water after handling. Avoid contact with skin, eyes or clothing. While handling product keep out of reach of children and pets. Do not eat or drink while handling this material. See section 6 of this SDS for clean up instructions.

Conditions for Safe Storage, Including any Incompatibilities

Storage Conditions	Keep tightly closed in a dry and cool place. Close container after each use. Store containers away from excessive heat & freezing. Do not store @ temperatures above 120 ° F. Protect from direct sunlight. Store away from incompatible materials. To maximize shelf life, store @ temperatures below 26C (80F).
Incompatible Materials	Strong acids.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines Exposure guidelines / protective equipment are for routine handling and accidental spills

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Calcium Carbonate 1317-65-3	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Titanium dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³
Ammonium Hydroxide 7664-41-7	STEL: 35 ppm TWA: 25 ppm	TWA: 50 ppm TWA: 35 mg/m ³ (vacated) STEL: 35 ppm (vacated) STEL: 27 mg/m ³	IDLH: 300 ppm TWA: 25 ppm TWA: 18 mg/m ³ STEL: 35 ppm STEL: 27 mg/m ³
Carbon Black 1333-86-4	TWA: 3 mg/m ³ inhalable fraction	TWA: 3.5 mg/m ³ (vacated) TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
Petroleum Hydrocarbon 64742-48-9	ACGIH TWA: 5 mg/m ³ ; ACGIH STEL: 10 mg/m ³	-	-

Appropriate Engineering Controls

Engineering Controls Ventilation must be adequate to maintain the ambient workplace atmosphere below the exposure limit(s) outlined in the SDS.

Individual Protection Measures, such as Personal Protective Equipment

Eye/Face Protection Use approved safety goggles or safety glasses. If necessary, refer to appropriate regulations & standards.

Skin and Body Protection Skin: Wear chemical impervious gloves (eg: Nitrile or Neoprene). Use triple gloves for spill response. If necessary, refer to appropriate regulations & standards.

Body: Use protection appropriate for task (eg: lab coat, coveralls, Tyvek suit). If necessary, refer to OSHA Technical Manual (Sec. VII: Personal Protective Equipment) or appropriate Standards of Canada. Use foot protection, as described in appropriate regulations & standards.

Respiratory Protection If mists or sprays are created, use appropriate respiratory protection. Oxygen levels below 19.5% considered IDLH by OSHA. In such instances, use full-facepiece pressure demand SCBA or a full facepiece, supplied air respirator w/ auxillary self-contained air supply.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	Smooth paste	Odor	Mild acrylic
Appearance	White & Various Other Colors	Odor Threshold	Not determined
Color	White & Colors		

<u>Property</u>	<u>Note: The information below is not intended for use in preparing product specifications</u>	<u>Remarks • Method</u>
pH	7.0-9.0	
Melting Point/Freezing Point	< 0 °C / <32 °F	
Boiling Point/Boiling Range	Not Established	
Flash Point	> 93.33 °C / > 200 °F	
Evaporation Rate	Not determined	
Flammability (Solid, Gas)	Not determined	
Upper Flammability Limits	Unknown	
Lower Flammability Limit	Unknown	
Vapor Pressure	Not established	
Vapor Density	Heavier than air	
Specific Gravity	~1.40-1.50	@ 25 °C (77 °F)
Water Solubility	Soluble in water	
Solubility in Other Solvents	Not determined	
Partition Coefficient	Not determined	
Autoignition Temperature	Unknown	
Decomposition Temperature	Not determined	
Kinematic Viscosity	Not determined	
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	
VOC Content (%)	<1.5%	
VOC Content	<25 g/L	

10. STABILITY AND REACTIVITY**Reactivity**

Cures upon contact with air.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to Avoid

Incompatible Materials. Excessive heat or cold.

Incompatible Materials

Strong acids.

Hazardous Decomposition Products

Thermal decomposition can generate irritating dust, fumes and toxic gases (carbon, titanium, and iron oxides, depending upon formulation).

11. TOXICOLOGICAL INFORMATION**Information on Likely Routes of Exposure**

Product Information

Eye Contact	Eye contact may result in tearing, redness & pain.
Skin Contact	Prolonged and frequent contact may cause redness and irritation. Repeated skin contact may cause dermatitis.
Inhalation	Overexposure to vapors during application & curing may mildly irritate respiratory tract & result in coughing & sneezing.
Ingestion	May cause gastrointestinal irritation, nausea, diarrhea, and vomiting.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Ammonium Hydroxide 7664-41-7	= 350 mg/kg (Rat)	-	= 5.1 mg/L (Rat) 1 h = 2000 ppm (Rat) 4 h
Carbon Black 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-
Petroleum Hydrocarbon 64742-48-9	> 5000 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	-

Information on Physical, Chemical and Toxicological Effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-term Exposure

Sensitization Not known to be human skin or respiratory sensitizers.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen. Titanium dioxide is a possible carcinogen when it appears as a respirable dust. Carbon black is a possible carcinogen when it appears as a respirable dust. Trace residual Formaldehyde present in base emulsion viewed as possible cancer hazard.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide 13463-67-7		Group 2B		X
Carbon Black 1333-86-4	A3	Group 2B		X

IARC (International Agency for Research on Cancer)
Group 2B - Possibly Carcinogenic to Humans
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
X - Present

Target Organ Effects Acute: Eyes & Skin. Chronic: Skin.

Numerical Measures of Toxicity

Not determined

12. ECOLOGICAL INFORMATION**Ecotoxicity**

PRACTICES SHOULD BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

Product not tested for aquatic or animal toxicity. Release of product to terrestrial, atmospheric & aquatic environments should be avoided.

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Ammonium Hydroxide 7664-41-7		0.44: 96 h Cyprinus carpio mg/L LC50 0.26 - 4.6: 96 h Lepomis macrochirus mg/L LC50 1.17: 96 h Lepomis macrochirus mg/L LC50 flow-through 0.73 - 2.35: 96 h Pimephales promelas mg/L LC50 5.9: 96 h Pimephales promelas mg/L LC50 static 1.5: 96 h Poecilia reticulata mg/L LC50 1.19: 96 h Poecilia reticulata mg/L LC50 static		25.4: 48 h Daphnia magna mg/L LC50
Carbon Black 1333-86-4				5600: 24 h Daphnia magna mg/L EC50
Petroleum Hydrocarbon 64742-48-9		2200: 96 h Pimephales promelas mg/L LC50		2.6: 96 h Chaetogammarus marinus mg/L LC50

Persistence and Degradability

Not tested for persistence & biodegradability

Bioaccumulation

Not tested for bio-accumulation potential

Mobility

Not tested for mobility in soil

Chemical Name	Partition Coefficient
Ammonium Hydroxide 7664-41-7	-1.14

Other Adverse Effects

Environmental Exposure Controls: Should be maintained so as to prevent release to the environment (atmospheric release, release to waterways & spills)

Ozone

Not expected to produce any ozone depletion

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated Packaging	Disposal should be in accordance with applicable regional, national and local laws and regulations.
US EPA Waste Number	Not applicable.

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT Not regulated

IATA Not regulated**IMDG** Not regulated**15. REGULATORY INFORMATION****International Inventories**

TSCA Listed
DSL Listed
NDSL Listed

Legend:*TSCA - United States Toxic Substances Control Act Section 8(b) Inventory**DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List**EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances**ENCS - Japan Existing and New Chemical Substances**IECSC - China Inventory of Existing Chemical Substances**KECL - Korean Existing and Evaluated Chemical Substances**PICCS - Philippines Inventory of Chemicals and Chemical Substances***US Federal Regulations****CERCLA**

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Ammonium Hydroxide 7664-41-7	100 lb	100 lb	RQ 100 lb final RQ RQ 45.4 kg final RQ

SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard No
Fire hazard No
Sudden release of pressure hazard No
Reactive Hazard No

SARA 313

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Ammonium Hydroxide - 7664-41-7	7664-41-7	<0.25	1.0

CWA (Clean Water Act)

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Ammonium Hydroxide 7664-41-7 (<0.25)	100 lb			X

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Titanium dioxide - 13463-67-7	Carcinogen
Carbon Black - 1333-86-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Calcium Carbonate 1317-65-3	X	X	X
Titanium dioxide 13463-67-7	X	X	X
Ammonium Hydroxide 7664-41-7	X	X	X
Carbon Black 1333-86-4	X	X	X

16. OTHER INFORMATION

NFPA	Health Hazards	Flammability	Instability	Special Hazards
	1	1	0	Not determined
HMIS	Health Hazards	Flammability	Physical Hazards	Personal Protection
	1	1	0	Not determined

Issue Date 27-Dec-2020
 Revision Date 27-Dec-2020
 Revision Note New product

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet