

# SOUND CONTROL<sup>®</sup>



## XLS Cap Model Muff (NRR – 23dB)

The XLS Muff from MSA provides a good combination of quality and comfort. It has many features only found in more expensive ear muffs. Designed to fit with MSA helmets and faceshields, it features easy-to-remove ear cushions for quick cleaning and replacement. The XLS Muff offers aggressive protection in low-moderate noise environments.

### Helmet-Mounted

- Spring design offers low pressure and a high level of comfort
- Three distinct wearing positions for ease of use
- Excellent grip makes it easy to adjust the cups, even when wearing gloves
- Unique moulded inserts give excellent noise attenuation and provides maximum space for the ears inside the cup
- Weight: 8.7 oz.

Slotted cap model..... 10061535  
 Hygiene Kit, complete with cushions & inserts ..... 10061537

### EN352.1 Data

SNR = 25 dB, H = 27 dB, M = 22 dB, L = 15 dB

Noise Reduction Rating (NRR) is tested in accordance with ANSI S3.19-1974, and meets CSA Class A.

### ANSI S3.19-1974 Data

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000
Mean	17	22	28	31	33	35	38	40	41
Stand. dev. (dB)	3.9	2.8	3.4	2.3	3.1	3.9	2.6	3.5	3.7

*Cap Model Noise reduction Ratings listed above are for medium V-Gard helmets only. Noise Reduction Rating and Attenuation Values for MSA Topgard, V-Gard 500, Thermalgard, Vanguard II and Super-V slotted helmets may vary. Contact MSA for more information.*

PASSIVE HEARING PROTECTION

