








Multi-Purpose Duct Tape



Backing: PE Coated Cloth

Adhesive: Rubber

Liner: N/A

Colors: Silver, Black

Specifications: Tested in accordance with UL 723

Standard Sizes: 48mm x 55m, 72mm x 55m

Applications

General repair

Bundling, patching & mending

General purpose construction uses

Seaming & hanging polyethylene sheeting

Floor and aisle marking

Features

Benefits

- **PE-Coated Cloth Backing**

Natural rubber based adhesive

Low VOC Content

- Conforms well to irregular surfaces
- Resists twisting & curling
- High adhesion & holding power for both rough and smooth surfaces
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Physical Properties

	Standard UOM	Metric UOM	Test Method	
Total Thickness	10 mils	225.4 mic	ASTM D-1000	
Adhesion to Steel	46 oz/in	5.03 N/cm	PSTC-101	
Tensile Strength	23 lb/in	40.28 N/cm	ASTM D-1000	
Operating Temperature	40-200°F	4-93°C		
VOC Content	<1 g/L			

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F Standard Shelf Life (at 25C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.

