


# Skullgard® Protective Caps and Hats

Handmade for durability, toughness and quality



Skullgard Caps and Hats are designed for use in grueling conditions. They have been tested to withstand radiant heat loads up to, but not exceeding, 350°F. Additionally, these helmets meet the voluntary reverse donning  and low temperature conditioning (LT) requirements of ANSI/ISEA Z89.1.

- Classification:** Type I, Top Impact
- Application:** General purpose, elevated temperature<sup>1</sup>
- Market(s):** Steel mills, welding, construction, open-pit mining, oil/gas/petrochemical refineries, rubber manufacturing, steam tunnels
- Shell Material:** Phenolic
- Available Styles:** Non-slotted Cap, Non-slotted Full-Brim Hat, and Non-Slotted Cap or Hat w/ lamp bracket and cord holder
- Sizes:** Cap: Standard (6½ – 8"); Large (7 – 8½")  
Hat: Standard (6½ – 8")
- Standards:** ANSI/ISEA Z89.1-2009 (Class G)
- Certification:** Third-party by SEI
- Customization:** Imprinting and striping available. Imprinting locations on Skullgard helmets are limited to the front only. A minimum order quantity of 16 Skullgard helmets of the same color, style and suspension selection is required.



## Skullgard Full Brim Hats

	P/N	Description
 <i>Standard Size</i>	475407	• Fas-Trac Ratchet Suspension
	454664	• Staz-On Pinlock Suspension
	460389	• Staz-On Pinlock Suspension • Lamp bracket and cord holder attached
 <i>Standard Size</i>	475408	• Fas-Trac Ratchet Suspension
	454665	• Staz-On Pinlock Suspension
 <i>Standard Size</i>	454666	• Staz-On Pinlock Suspension
 <i>Standard Size</i>	454668	
 <i>Standard Size</i>	454673	



**DID YOU KNOW?** An MSA helmet should not be altered or modified in any way. However, it is permissible to use pressure-sensitive, NON-METALLIC stickers or tape with self-adhesive backing as long as they are placed no closer than ½" from the helmet's edge. According to MSA test results, non-metallic stickers or tape placed in such locations will not affect the burn-through (i.e. dielectric classification) of an MSA helmet's structure.

<sup>1</sup> Skullgard Caps and Hats can withstand radiant heat loads up to but not exceeding 350°F.

Because every life has a **purpose...**

## Skullgard Caps

	P/N	Description
 <i>Standard Size</i>	475395	• Fas-Trac Ratchet Suspension
	482002	• Fas-Trac Ratchet Suspension • Welders' Lugs attached
	816651	• Swing Ratchet Suspension
	454617	• Staz-On Pinlock Suspension
	460409	• Staz-On Pinlock Suspension • Lamp Bracket and cord holder attached
 <i>Large Size</i>	475405	• Fas-Trac Ratchet Suspension
	82018	• Staz-On Pinlock Suspension
 <i>Standard Size</i>	475396	• Fas-Trac Ratchet Suspension
	454618	• Staz-On Pinlock Suspension
 <i>Standard Size</i>	475397	• Fas-Trac Ratchet Suspension
	454619	• Staz-On Pinlock Suspension
 <i>Standard Size</i>	454620	• Staz-On Pinlock Suspension
 <i>Standard Size</i>	454621	
 <i>Standard Size</i>	454622	
 <i>Standard Size</i>	454623	
 <i>Standard Size</i>	454626	
 <i>Standard Size</i>	458702 <sup>2</sup>	
<sup>2</sup> Skullgard Cap meets the voluntary requirements for hi-visibility as outlined in ANSI/ISEA Z89.1. Look for the official hi-visibility marking [HV] on the helmet label.		

## Replacement Suspensions

	P/N	Description
	473334	Fas-Trac Ratchet Suspension Std Size (6½" - 8")
	478454	Fas-Trac Ratchet Suspension Large Size (7" - 8½")
	454231	Staz-On Pinlock Suspension Std Size (6½" - 8")
	468096	Staz-On Pinlock Suspension Large Size (7" - 8½")
	816654	Swing Ratchet Suspension Large Size (6½" - 7½")

### ⚠ WARNING

Ensure suspensions and helmet match by manufacturer. Do not mix suspension sizes and helmet sizes (i.e., putting a standard sized suspension in a large helmet or any other mismatched combination). Do not use competitor suspensions in MSA helmets. Use only the indicated MSA suspension in your MSA helmet. Failure to follow these instructions will reduce the ability of the protective helmet to receive impact, and could result in serious injury or death. Replace your suspension every 12 months. In the case of an impact, replace entire helmet assembly immediately.

Please contact MSA Customer Service at 1-800-MSA-2222 for details about these or other Skullgard product configurations. You can also visit us on the web at [MSASafety.com](http://MSASafety.com).

Note: This Bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products.

ID 0601-12-MC / Feb 2014

© MSA 2014 Printed in U.S.A.



**MSA Corporate Center**  
1000 Cranberry Woods Drive  
Cranberry Township, PA 16066 USA  
Phone 724-776-8600  
[www.MSAsafety.com](http://www.MSAsafety.com)

**U.S. Customer Service Center**  
Phone 1-800-MSA-2222  
Fax 1-800-967-0398

**MSA Canada**  
Phone 1-800-672-2222  
Fax 1-800-967-0398

**MSA Mexico**  
Phone 011 52 442 227 3949  
Fax 011 52 442 227 3943

**MSA International**  
Phone 724-776-8626  
Toll Free 1-800-672-7777  
Fax 724-741-1559

[www.MSAsafety.com](http://www.MSAsafety.com)