



This 2,989-pound scraper rivals other manufacturers' heavier machines. Different from scrapers that are powered using a hydrostat driver system, the 8000 offers the speed and power of propane while also combining patented carbide angle-shank technology with the added efficiency of dual-lift hydraulic slide plates. Consistent torque sets the operational standard for high removal rates, and each machine undergoes a rigorous quality assurance program including emissions certification.

8000 Specifications		
Power Supply	Propane	
Width*	30"	76 cm
Height	65.5"	166 cm
Length	63"	160 cm
Weight**	2,963 lb	1344 kg
Removable Weight	1,043 lb	473.1 kg
Weight (machine only)	1,920 lb	870.9 kg
Speed	up to 200 ft/min	up to 61 m/min
HP	25	18.6 kW

### SAFETY

- A.** Automatic kill switch is triggered when the operator seat is vacant
- B.** Larger/deepened forklift pockets
- C.** Liquid-cooled Kawasaki engine is re-engineered with National's exclusive catalytic design for the industry's lowest emissions
- D.** Front debris deflector protects machine from loose material

### COMFORT

- E.** Ergonomic design includes movable foot pegs, taller handles, and an adjustable seat that allows for optimal operator comfort and the best possible line of sight
- F.** Hinged hood system for easy-access maintenance

### PERFORMANCE

- G.** Precise hydraulic steering for maneuvering in tight spaces, zero turn radius, and continuous torque for higher removal rates and greater productivity
- H.** Quick-change swivel head blade holder
- I.** Dual-lift, hydraulic slide plate adjusts blade pitch and angle for continuous contact with the floor; standard on every 8000; this also adds on additional 150+ pounds of down pressure on the cutting head
- J.** 21-inch nonmarking tires
- K.** Compact design fits through standard door frames and elevator doors
- L.** Hydraulic brake system automatically engages when the machine is in the off position
- M.** Front caster wheels allow increased maneuverability in tight spaces
- N.** Improved exhaust system meets federal OSHA regulations
- O.** LED light for increased visibility on the jobsite

### INCLUDED WITH THE 8000

- 5110-100: Transport Wheels
- 402929: 3/4 x 1-1/8 Wrench
- Kit 5175 includes:
  - 6277-BU: 45 degree, 3" x 12" self-scoring, bevel up
  - 6284: 3" x 12" heavy-duty blade
  - 7050-12: 12" cutting head
  - 7079-2: 2" x 6" angle shank w/ carbide tip
- 74854: Weight, 37 pounds (10) (front)
- 400197: Weight, 28 pounds (9) (front)
- 402102: Weight, 84 pounds (4) (front)
- 5110-404: Weight, 75 pounds (1) (rear)
- 402139: Propane tanks (1)
- 75007: CO detector (2)
- 75008: Clip (2)
- 5700-88: Hour meter
- Instruction manual
- One-year manufacturer's warranty on parts and labor