

NEW!

# Miller AirCore™ Tower Climbing Harness

*For use on Cell Phone, TV, Radio and Utility Towers*

The new Miller AirCore™ Tower Climbing harness provides the ultimate in performance, comfort and durability – exceeding expectations even when used in the most challenging climbing environments! This new line of AirCore harnesses keeps your workers comfortable and safe – increasing productivity. It is designed for workers climbing cell phone, TV, radio and utility towers, while building/decommissioning towers, changing out transmission lines/antennas, or installing/replacing lights.



ACT-QCBCUG

*Research has found that a comfortable harness is more likely to be worn properly, increasing compliance, safety, and productivity.*

## Features/Benefits:

- **COMFORT** – breathable, open-core padding technology provides optimal air flow, while reducing heat and moisture entrapment, keeping a worker drier and cooler. **Up to 16% less surface area** than other padding used on the market. AirCore harnesses are designed with patented Miller DuraFlex® stretchable webbing that provides greater flexibility and increased comfort.
- **EASY ADJUSTABILITY** – improved lightweight, **low profile cam buckles** on the shoulder straps make vertical webbing adjustment the easiest of any harness on the market. Quick-connect chest buckles for easy donning.
- **LIGHTWEIGHT** – Materials and components selected to reduce fatigue for all-day endurance and increased productivity. **Up to 21% lighter** in weight than similar competitive harnesses.
- **STYLISH DESIGN** – Webbing design creates an original and vibrant color for **easy identification, greater visibility** and increased safety.
- **VERSATILE CONVENIENCE** – Leather **Bos'n chair attachment** – removable/adjustable leather rigid work seat for added support; **removable belt with tool loops** – uniquely designed to stay in position when disconnected, even when tools are attached; **oversized ID tag** – provides quick and easy harness size identification.

## Miller AirCore™ Tower Climbing Harnesses

SKU	Description	Special Feature	Weight
<b>AirCore Tower Climbing Harnesses with Steel Hardware</b>			
ACT-QCBCUG	Quick Connect Chest and Leg Straps, Front D-ring, Lumbar Pad, Side D-rings, Removable Belt	Removable Bos'n Chair with Side D-rings	9.8 lbs. (4.4 kg)
ACT-QCUG	Quick Connect Chest and Leg Straps, Front D-ring, Lumbar Pad, Side D-rings, Removable Belt	NA	6.6 lbs. (3.0 kg)
<b>AirCore Tower Climbing Harnesses with Aluminum Hardware</b>			
AAT-QCBCUG	Quick Connect Chest and Leg Straps, Front D-ring, Lumbar Pad, Side D-rings, Removable Belt	Removable Bos'n Chair with Side D-rings	8.8 lbs. (4.0 kg)
AAT-QCUG	Quick Connect Chest and Leg Straps, Front D-ring, Lumbar Pad, Side D-rings, Removable Belt	NA	5.9 lbs. (2.7 kg)

Model numbers listed are for **universal size**. Harnesses are also available in small/medium and XXlarge by replacing the "U" in the model number with "**SM**" or "**23X**". To order a blue harness, simply replace the "G" in the model number with "**B**" (ex. ACT-QCUB). All listed models include a back D-ring and sub-pelvic strap.

Miller AirCore Tower Climbing Harnesses meet applicable OSHA 1926.502, ANSI A10.32, ANSI Z359.1 and CSA Z259.10-12 requirements.

**Rated to 400 lbs. (181.4 kg) capacity.**

SKU	Description	Weight
<b>Accessories</b>		
ACT-BC	Bos'n Chair with Steel Side D-rings	3.2 lbs. (1.5 kg)
AAT-BC	Bos'n Chair with Aluminum Side D-rings	2.9 lbs. (1.3 kg)
ACTL10	Tool Loops; 10 pack	0.5 lbs. (0.2 kg)
6758WRS/ 18INGN*	Spreader Bar Hook Attached to 18-in. (0.5m) Web Lanyard with Locking Rebar Hook	3.5 lbs. (1.6 kg)
1014937*	Non-Removable Adjustable Rope Lanyard with Kernmantle Rope, Steel Twist-Lock Carabiner and Locking Rebar Hook; 6-ft. (1.8m)	4.5 lbs. (2.0 kg)
6756RS-Z7*	Rebar Chain Assembly with Locking Rebar Hook, Attached Swivel, and Two (2) Locking Snap Hooks	3.7 lbs. (1.7 kg)
6757WRS-Z7/35INGN*	Rebar Web Assembly with Locking Rebar Hook and Two Locking Snap Hooks	3.3 lbs. (1.5 kg)

\*Models which include connectors with 3,600 lb. gate-strength

**Lead them to safety** – build an enduring Culture of Safety where employees make safe choices on their own.

[www.honeywellsafety.com/culture](http://www.honeywellsafety.com/culture)

©2014 Honeywell International Inc. All rights reserved.

*This equipment should only be used after reading the manufacturer's instructions. Failure to follow instructions could result in serious injury or fatality*



by Honeywell

► **Ask the Expert ... Ask Miller.**

**800/873-5242: Honeywell Technical Service**

**800/430-5490: Honeywell Customer Care**

[www.millerfallprotection.com](http://www.millerfallprotection.com)

GET CONNECTED:



LMACT

**Honeywell**