SAFETY DATA SHEET

This Safety Data Sheet conforms to ANSI Z400.5, and to the format requirements and the International Chemical Safety Cards of the Global Harmonizing System. THIS SDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD) IMPORTANT: Read this SDS before handling & disposing of this product. Pass this information on to employees, customers, & users of this product.

SECTION 1. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER

PRODUCT IDENTITY: MEGAPACK CC500 (RTU 1 TO 32)

PRODUCT PURPOSE: CARPET PRE-SPRAY COMPANY IDENTITY: Groom Industries COMPANY ADDRESS: 4282 S 590 W

COMPANY CITY: Salt Lake City, UT 84123

COMPANY PHONE: 1-800-397-3759

EMERGENCY PHONES: INFOTRAC: 1-800-535-5053 (USA)

SECTION 2. HAZARDS IDENTIFICATION

CAUTION

HAZARD STATEMENTS:

H100s = General, H200s = Physical, H300s = Health, H400s = Environmental

H320 Causes eye irritation. H332 Harmful if inhaled.

PRECAUTIONARY STATEMENTS:

P100s = General, P200s = Prevention, P300s = Response, P400s = Storage, P500s = Disposal

P260 Do not breathe dust/fume/gas/mist/vapors/spray. P262 Do not get in eyes, on skin, or on clothing.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

There are no components contained in this material >0.41 % that are considered hazardous under 29CFR1910.1200.

TRACE COMPONENTS: Trace ingredients (if any) are present in < 1% concentration, (< 0.1% for potential carcinogens, reproductive toxins, respiratory tract mutagens, and sensitizers). None of the trace ingredients contribute significant additional hazards at the concentrations that may be present in this product. All pertinent hazard information has been provided in this document, per the requirements of the Federal Occupational Safety and Health Administration Standard (29 CFR 1910.1200), U.S. State equivalents, and Canadian Hazardous Materials Identification System Standard (CPR 4).

SEE SECTIONS 8, 11 & 12 FOR TOXICOLOGICAL INFORMATION.

SECTION 4. FIRST AID MEASURES

EYE CONTACT:

For eyes, flush with plenty of water for 15 minutes & get medical attention.

SKIN CONTACT:

In case of contact with skin immediately remove contaminated clothing. Wash thoroughly with soap & water. Wash contaminated clothing before reuse.

INHALATION:

After high vapor exposure, remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, trained personnel should immediately begin artificial respiration. If the heart has stopped, trained personnel should immediately begin cardiopulmonary resuscitation (CPR).

SECTION 4. FIRST AID MEASURES (CONTINUED)

SWALLOWING:

Rinse mouth. GET MEDICAL ATTENTION IMMEDIATELY. Do NOT give liquids to an unconscious or convulsing person.

SECTION 5. FIRE FIGHTING MEASURES

FIRE & EXPLOSION PREVENTIVE MEASURES Not Applicable.

EXTINGUISHING MEDIA

Use appropriate extinguishing media for surrounding fire.

SPECIAL FIRE FIGHTING PROCEDURES

Water spray may be ineffective on fire but can protect fire-fighters & cool closed containers. Use fog nozzles if water is used. Do not enter confined fire-space without full bunker gear. (Helmet with face shield, bunker coats, gloves & rubber boots). Use NIOSH approved positive-pressure self-contained breathing apparatus.

UNUSUAL EXPLOSION AND FIRE PROCEDURES

Closed containers may explode if exposed to extreme heat. Applying to hot surfaces requires special precautions.

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE MEASURES:

Keep unprotected personnel away.

Wear appropriate personal protective equipment given in Section 8.

ENVIRONMENTAL PRECAUTIONS:

Keep from entering storm sewers and ditches which lead to waterways.

CONTAINMENT AND CLEAN-UP MEASURES:

Stop spill at source. Dike and contain.

Collect leaking & spilled liquid in sealable containers as far as possible.

SECTION 7. HANDLING AND STORAGE

HANDLING

Use with adequate ventilation. Avoid prolonged or repeated contact with skin. Mark container with secondary OSHA label.

STORAGE

Isolate from strong oxidants. Do not store above 49 C/120 F. Keep container tightly closed & upright when not in use to prevent leakage.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

There are no components contained in this material >0.41% that are considered hazardous under 29CFR1910.1200. There are no known risks for TWA (OSHA) and TLV (ACGIH).

This product contains no EPA Hazardous Air Pollutants (HAP) in amounts > 0.1%.

RESPIRATORY EXPOSURE CONTROLS

A respiratory protection program that meets OSHA 29 CFR 1910.134 and ANSI Z86.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant a respirator's use.

VENTILATION

LOCAL EXHAUST: Necessary MECHANICAL (GENERAL): Acceptable SPECIAL: None OTHER: None Please refer to ACGIH document, "Industrial Ventilation, A Manual of Recommended Practices", most recent edition, for details.

```
PERSONAL PROTECTIONS:
```

Wear OSHA Standard goggles & gloves as a standard practice.

SECTION 9. PHYSICAL & CHEMICAL PROPERTIES

```
APPEARANCE:
                                                   Clear Light Beige Liquid
ODOR:
                                                   Light Mint
                                                   Not Available
ODOR THRESHOLD:
pH (Neutrality):
                                                   9.0 to 9.2
MELTING POINT/FREEZING POINT:
                                                  Not Available
                                                  102 102 360* C/216 216 681* F(*=End Point)
BOILING RANGE (IBP,50%, Dry Point):
FLASH POINT (TEST METHOD):
                                                  > 93 C / > 201 F (PMCC)
EVAPORATION RATE (n-BUTYL ACETATE=1):
                                                  Not Applicable
FLAMMABILITY CLASSIFICATION:
                                                  Class III-B
LOWER FLAMMABLE LIMIT IN AIR (% by vol):
                                                  0.95 (Lowest Component)
UPPER FLAMMABLE LIMIT IN AIR (% by vol):
                                                  Not Available
VAPOR PRESSURE (mm of Hg)@20 C
                                                  Not Available
VAPOR DENSITY (air=1):
                                                  Not Available
GRAVITY @ 68/68 F / 20/20 C:
                                                  1.001
  DENSITY:
   SPECIFIC GRAVITY (Water=1):
                                                  1.002
   POUNDS/GALLON:
                                                  8.347
WATER SOLUBILITY:
                                                  Complete
PARTITION COEFFICIENT (n-Octane/Water):
                                                  Not Available
AUTO IGNITION TEMPERATURE:
                                                  398 C / 750 F
DECOMPOSITION TEMPERATURE:
                                                  Not Available
VOCs (>0.044 Lbs/Sq In) :
                                                   Not Available
TOTAL VOC'S (TVOC)*:
                                                   0.007 Lbs/Gal
NONEXEMPT VOC'S (CVOC)*:
                                                   0.007 Lbs/Gal
HAZARDOUS AIR POLLUTANTS (HAPS):
                                                   0.0 Wt%
NONEXEMPT VOC PARTIAL PRESSURE (mm of Hg @ 20 C) Not Available
VISCOSITY @ 20 C (ASTM D445):
                                                  Not Available
* Using CARB (California Air Resources Board Rules).
```

SECTION 10. STABILITY & REACTIVITY

```
STABILITY
```

Stable under normal conditions.

CONDITIONS TO AVOID

Isolate from extreme heat and open flame.

MATERIALS TO AVOID

Isolate from strong oxidizer.

HAZARDOUS DECOMPOSITION PRODUCTS Carbon Oxides from heating.

HAZARDOUS POLYMERIZATION Will not occur.

SECTION 11. TOXICOLOGICAL INFORMATION

ACUTE HAZARDS

```
EYE & SKIN CONTACT:
```

Primary irritation to skin, defatting, dermatitis. Primary irritation to eyes, redness, tearing, blurred vision. Liquid can cause eye irritation. Wash thoroughly after handling.

INHALATION:

Anesthetic. Irritates respiratory tract. Acute overexposure can cause serious nervous system depression. Vapor harmful.

SWALLOWING:

Swallowing can cause abdominal irritation, nausea, vomiting & diarrhea.

PRODUCT IDENTITY: MEGAPACK CC500 (RTU 1 TO 32)

SECTION 11. TOXICOLOGICAL INFORMATION (CONTINUED)

SUBCHRONIC HAZARDS/CONDITIONS AGGRAVATED

CONDITIONS AGGRAVATED:

None Known.

CHRONIC HAZARDS

CANCER, REPRODUCTIVE & OTHER CHRONIC HAZARDS:
This product has no carcinogens listed by IARC, NTP, NIOSH,
OSHA or ACGIH, as of this date, greater or equal to 0.1%.

IRRITANCY OF PRODUCT: This product is irritating to contaminated tissue.

SENSITIZATION TO THE PRODUCT: No component of this product is known to be a sensitizer.

MUTAGENICITY: This product is not reported to produce mutagenic effects in humans.

EMBRYOTOXICITY: This product is not reported to produce embryotoxic effects in humans.

TERATOGENICITY: This product is not reported to produce teratogenic effects in humans.

REPRODUCTIVE TOXICITY: This product is not reported to cause reproductive effects in humans.

A <u>mutagen</u> is a chemical which causes permanent changes to genetic material (DNA) such that the changes will propagate through generational lines. An <u>embryotoxin</u> is a chemical which causes damage to a developing embryo (such as: within the eight weeks of pregnancy in humans), but the damage does not propagate across generational lines. A <u>teratogen</u> is a chemical which causes damage to a developing fetus, but the damage does not propagate across generational lines. A <u>reproductive toxin</u> is any substance which interferes in any way with the reproductive process.

MAMMALIAN TOXICITY INFORMATION

No mammalian information is available on this product.

SECTION 12. ECOLOGICAL INFORMATION

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

EFFECT OF MATERIAL ON PLANTS AND ANIMALS:

This product may be harmful or fatal to plant and animal life if released into the environment. Refer to Section 11 (Toxicological Information) for further data on the effects of this product's components on test animals.

EFFECT OF MATERIAL ON AQUATIC LIFE:

No aquatic environmental information is available on this product.

MOBILITY IN SOIL

This material is a mobile liquid.

DEGRADABILITY

This product is completely biodegradable.

ACCUMULATION

Bioaccumulation of this product has not been determined.

GREEN INGREDIENTS

>99.7% of ingredients are approved or on an approved list of at least one third party green certification organization in ready to use dilution of 1 to 32.

SECTION 13. DISPOSAL CONSIDERATIONS

Processing, use or contamination may change the waste disposal requirements. Do not dispose of on land, in surface waters, or in storm drains. Waste should be recycled or disposed of in accordance with regulations. Large amounts should be collected for reuse or consigned to licensed hazardous waste haulers for disposal.

ALL DISPOSAL MUST BE IN ACCORDANCE WITH ALL FEDERAL, STATE, PROVINCIAL, AND LOCAL REGULATIONS. IF IN DOUBT, CONTACT PROPER AGENCIES.

PRODUCT IDENTITY: MEGAPACK CC500 (RTU 1 TO 32)

SECTION 14. TRANSPORT INFORMATION

SECONDARY CONTAINERS SHOULD BE MARKED WITH APPROPRIATE OSHA LABELING.

SECTION 15. REGULATORY INFORMATION

EPA REGULATION:

SARA SECTION 311/312 HAZARDS: None Known

All components of this product are on the TSCA list. This material contains no known products restricted under SARA Title III, Section 313 in amounts greater or equal to 1%.

STATE REGULATIONS:

THIS PRODUCT MEETS REQUIREMENTS OF SOUTHERN CALIFORNIA AQMD RULE 443.1 & SIMILAR REGULATIONS

THIS PRODUCT DOES NOT MEET VOC STANDARDS IN 18 STATES AND IS NOT SOLD IN THESE STATES.

CALIFORNIA SAFE DRINKING WATER & TOXIC ENFORCEMENT ACT (PROPOSITION 65): This product contains no chemicals known to the State of California to cause cancer or reproductive toxicity.

INTERNATIONAL REGULATIONS

The components of this product are listed on the chemical inventories of the following countries:

Australia (AICS), Canada (DSL or NDSL), China (IECSC), Europe (EINECS, ELINCS)G Japan (METI/CSCL, MHLW/ISHL), South Korea (KECI), New Zealand (NZIoC), Philippines (PICCS), Switzerland (SWISS), Taiwan (NECSI), USA (TSCA).

CANADA: WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS) D2B: Irritating to skin / eyes.

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

SECTION 16. OTHER INFORMATION

HAZARD RATINGS:

HEALTH (NFPA): 0, HEALTH (HMIS): 1, FLAMMABILITY: 1, PHYSICAL HAZARD: 0 (Personal Protection Rating to be supplied by user based on use conditions.) This information is intended solely for the use of individuals trained in the NFPA & HMIS hazard rating systems.

EMPLOYEE TRAINING

See Section 2 for Risk & Safety Statements. Employees should be made aware of all hazards of this material (as stated in this SDS) before handling it.

SDS DATE: 4/25/2014

NOTICE

Groom Industries disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency.

Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon information contained herein.

This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.