ATTACK

Premium Powdered Enzyme Prespray

ATTACK is a high powered pre-conditioner which combines active enzymes, surfactants, softeners and grease lifters that will thoroughly clean a broad spectrum of fibres. Attack effectively removes animal, vegetable and petroleum oils, cooking and food residues, leaving traffic areas and heavily soiled carpet completely clean.

- pH 11.0
- Dilution Ratio: up to 1:128
- Active enzymes digest food soils and greases
- Excellent for use on restaurant carpets
- Dissolves easily in warm to hot water
- Effectively removes most urine spots

Available in:

- 2.72 KG (6 LB Jar) Part # 2653-3253
- 14.51 KG (32 LB Pail) Part # 2654-3254
- 167.83 KG (370 LB Drum) Part # 2655-3255

DIRECTIONS: Pretest in an inconspicuous location for color fastness and fibre stability.

Pump-up or Power Sprayer: For Light Soil Conditions: Mix 1-2 oz of Attack into 1 gal (3.78 L) of warm to hot water. Mix until completely dissolved (up to 1:128 Dilution). For Heavy Soil Conditions: Mix 2-3 oz of Attack into 1 gal (3.78 L) of warm to hot water. Mix until completely dissolved (up to 1:64 Dilution). Hydro-Force[™] Sprayer: 4:1 Dilution (No Tip): Mix 10 oz of Attack into Hydro-Force[™] jug and fill with hot water. Shake until completely dissolved.



8:1 Dilution (Yellow Tip): Mix 18 oz of Attack into Hydro-Force[™] jug and fill with hot water. Shake until completely dissolved. For best results: Pile lift or vacuum carpet prior to cleaning. Spray diluted Attack preconditioner onto carpet at the rate of 800-1000 square feet per gallon (3.78L). Agitate presprayed area using a carpet groomer. Allow 15 minutes dwell time, then rinse with Esteam Fibre Rinse solution in conjunction with hot water extraction. Diluted pH: 11.0 Caution: Product not recommended for use on wool or natural fibres.

Keep this product out of reach of children. Read the Safety Data Sheet and Product Label before using. Take the necessary precautions dictated by the label to ensure that your health and that of your customers' is protected.

FOR SDS VISIT /POUR CONSULTER LES FDS VISITEZ LE: www.esteam.com



1-800-653-8338