

SAFE STRIP

Technical Information

Safe Strip

Product Description:

Safe Strip is a specially formulated stripper, designed to remove urethane coatings from the floor. It

Special Features:

- Very fast acting as compared to typical wax strippers.
- Not necessary to add water to activate

Where and When to Use:

To be used to remove any urethane coatings.

Packaging:

1gallon (3.8L)

Storage:

Storage temperature: Ambient

Directions for use:

Safe Strip can be diluted 1:1 with water, but for optimal performance, it is not necessary to dilute Safe Strip. Evenly apply to surface 100sq. ft. per 1/2 gallon of product. Allow to dwell for 15-20 minutes. Scrub using a nylon brush or nilo grit brush. If old, difficult-to-remove wax remains, then a 2nd or 3rd application may be necessary. Rinse with clear water.

Product Specifications:

Physical State: Liquid
Odor: Aromatic
Appearance: colorless
pH: 13.4
Solubility in water: Infinite
Specific gravity: 1.1

Precautions Summary:

CAUTION: UPON SKIN CONTACT, WASH AND REMOVE IMMEDIATELY.

Eyes: Will injure eye tissue if not removed promptly by washing with water.

Skin: Will burn skin upon contact.

Inhalation: Mists are irritating to eyes and respiratory tract in high concentrations.

Ingestion: Minimal toxicity. Very irritating to mouth, throat and stomach. May cause gastric tract disorder.

Flash point: Not flammable.

VMC TECHNICAL ASSISTANCE CORPORATION

8311 EASTPOINT DRIVE, SUITE 800
DALLAS, TX 75227

TELEPHONE
(214)381-8456

FAX
(214)381-4896

WEB
www.vmctac.com

SAFE STRIP
TECHNICAL INFORMATION